HANNspree

HO 225 DTB 21.5" Open Frame Touch Monitor

Experts in **Display**

Open Frame Touch Monitor

HO 225 DTB

54,6 cm / 21.5" Diagonal LED Backlight – Format 16:9

- 1920 x 1080 Resolution Full HD 1080p
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- Dual Input: DVI-D + VGA
- IP54 (front) Rating Level
- Display Protection: Thickness 3,3mm
- Built for 24/7
- 50.000 Hours Backlight Lifetime
- ≥6H Toughened Hard Panel Surface
- Slim Profile with Narrow Edges
- Sturdy Metal Case
- Touch-Through Glass (available upon request*)
- VESA Mount and Multiple Mounting Options
- Edge to Edge glass without raised frame
- Orientation: Landscape, Portrait, Face-Up







54,6 cm / 21.5"

Part. No..: HO 225 DTB

SIZE, RESOLUTION



21.5" 16:9 Aspect Ratio



Full HD 1920 x 1080

CONNECTIVITY, IP LEVEL



VGA DVI-D



IP 54 Water & Dust Protection

VIEWING ANGLE, VESA



178 Ultra-Wide Viewing Angle



VESA Wall-Mountable

OTHER FEATURES



Operating 24Hours / 7 Days



50.000 Hours Lifetime

Technical Specifications >>>


* For more details contact your local HSP office / representative or send us a request via the product enquiry form on the website.

HANNspree


HO 225 DTB 21.5" Open Frame Touch Monitor

Experts in **Display**

Display Size	54,61 cm / 21.5" Diagonal
Panel Type	TFT – LED Backlight
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	250cd/m²
Contrast (Typ.)	3.000:1 (Typical)
Display Area	476 x 268 mm
Viewing Angle L/R; U/D	178° H / 178° V
Response Time	8 msec
Pixel Pitch	0,247 (H) x 0,247 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch Material Glass + Glass
Display Colors	16.7M Colors
Horizontal Frequency	30 ~ 81 kHz
Vertical Frequency	55 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	VGA
Input 2	DVI-D
Input 3	USB (Touch)
Speakers	-
Power Consumption	On: 16W; Stand-by: 0,3W; Off: 0,2W
AC Power Range	12 Volt / 3A External Power Supply
Product Dimensions	526,6 x 42 x 318,2 mm (W x D x H)
Packing Dimensions	570 x 150 x 380 mm (W x D x H)
Net / Gross Weight	5,6 Kg / 7 Kg



VESA Mounting	75 x 75 mm / 100 x 100 mm Screws: M4, 4mm (Max), pitch 0,7 mm		
Display Protection	Thickness 3,3±0,3 mm		
Hardness / Transmittance	≥6H Toughened hard panel surface / ≥85%		
IP Rating Level	IP 54 (Front), Water and Dust Protection *		
24 / 7 Opearting	Yes		
LED Backlight life	50.000 hours		
Accessory	Power supply; VGA Cable (1,5m); USB Cable for Touch.		
Certifications	CE, RoHS, WEEE		
On Screen Display	9 Languages		
Color	9300, 7500, 6500, sRGB, User Mode		
Orientation	Landscape, Portrait, Face-Up		
Sur	onlier's Name	HANNIcoree	



Supplier's Name	HANNspree
Model Name	HO225DTB
Energy efficiency class for standard Dynamic Range (SDR)	Е
Annual Energy Power Consumption (kWh/1000h)	16 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	16 W
Off mode power demand (W)	0,2 W
Standby mode power demand (W)	0,3 W
Screen Diagonal (cm / inches)	54,6cm / 21.5"
Resolution	1920 x 1080




PART. NO.: HO 225 DTB

^{*} IP54: The IP Code classifies how resistant a device is to foreign objects and moisture. IP54 means that the monitor will operate in dusty conditions, and will resist splashing water.

HO 225 DTB 21.5" Open Frame Touch Monitor


Experts in **Display**







HO 225 DTB 21.5" Open Frame Touch Monitor



HO 225 DTB 21.5" Open Frame Touch Monitor

Experts in **Display**

